

RFF 1/2" FLEXIBLE COAXIAL CABLE

NK CODES

RFF 1/2"-50
 RFF 1/2"-50 GHF
 RFF 1/2"-50 BHF
 RFF 1/2"-50 BHF (UL) CATVR

NKRFF01200
 NKRFF01201
 NKRFF01202
 NKRFF01204

CONSTRUCTION



Inner conductor	Copper-clad aluminium wire	Ø 3.55 mm	(0.14 in)
Dielectric	Cellular polyethylene	Ø 9.0 mm	(0.35 in)
Outer conductor	Corrugated copper tube	Ø 11.9 mm	(0.47 in)
Jacket	See Jacketing Options table below	Ø 13.5 mm	(0.53 in)
Marking	Draka, cable type, manufacture week, year, batch number and meter mark		

ELECTRICAL CHARACTERISTICS at +20°C (+68°F)

Characteristic impedance	50 ± 1 Ω
Return loss 24 dB for 100 m cable with NKC connectors	
- 380 - 500	MHz
- 806 - 960	"
- 1710 - 1880	"
- 1900 - 2170	"
Other bands also available on request	
Bands according to customer's specifications	
Attenuation	See table
Velocity factor	0.82
Capacitance	82 pF/m (25 pF/ft)
Maximum frequency	12 500 MHz
Max power rating	See table
Peak RF voltage rating	1.39 kV
Peak power rating	19.0 kW
DC-resistance	
- Inner conductor	2.57 Ω/km (0.78 Ω/1000 ft)
- Outer conductor	3.10 Ω/km (0.94 Ω/1000 ft)

MECHANICAL CHARACTERISTICS

Weight	0.19 kg/m (0.13 lb/ft)
Maximum pulling force	900 N (198 lb)
Minimum bending radius	
- Single bending	15 mm (0.6 in)
- Repeated bending	30 mm (1.2 in)
Operating temperature range	-55...+80°C (-67...+176 °F)
Crush resistance	3.4 kg/mm (190 lb/in)
Bending moment	2.7 Nm (2.0 lb-ft)
Recommended clamp distance	1.0 m (3.3 ft)

JACKETING OPTIONS

TYPE	JACKET	IEC 60754 -1/-2 halogen free, non corrosive	IEC 61034 low smoke emission	IEC 60332-3-24 fire retardant	UV retardancy	UL rated	Min. installation temperature
RFF 1/2"-50	Black, halogen free polyethylene	yes	no	no	yes	no	-40°C (-40°F)
RFF 1/2"-50 GHF	Grey, halogen free fire retardant thermoplastic	yes	yes	yes	no	no	-20°C (-4°F)
RFF 1/2"-50 BHF	Black, halogen free fire retardant thermoplastic	yes	yes	yes	yes	no	-20°C (-4°F)
RFF 1/2"-50 BHF (UL) CATVR	Black, halogen free fire retardant UL Riser rated jacket	yes	yes	yes	yes	yes	-20°C (-4°F)

RFF 1/2" FLEXIBLE COAXIAL CABLE

FREQUENCY MHz	ATTENUATION dB/100 m	ATTENUATION dB/100 ft	POWER RATING kW
10	0.972	0.296	8.4
30	1.70	0.517	4.8
50	2.20	0.671	3.7
88	2.94	0.896	2.7
100	3.14	0.957	2.6
108	3.27	0.996	2.5
174	4.18	1.28	1.9
200	4.50	1.37	1.8
300	5.56	1.70	1.4
400	6.48	1.97	1.2
450	6.89	2.10	1.2
500	7.29	2.22	1.1
512	7.38	2.25	1.1
600	8.04	2.45	0.99
700	8.73	2.66	0.91
800	9.38	2.86	0.85
850	9.70	2.96	0.82
890	9.94	3.03	0.80
900	10.0	3.05	0.79
950	10.3	3.14	0.77
960	10.4	3.16	0.77
1000	10.6	3.23	0.75
1200	11.7	3.57	0.68
1400	12.7	3.88	0.62
1600	13.7	4.18	0.58
1800	14.7	4.47	0.54
1900	15.1	4.60	0.52
2000	15.5	4.74	0.51
2200	16.4	5.00	0.48
2400	17.2	5.25	0.46
2600	18.0	5.50	0.44
2800	18.8	5.73	0.42
3000	19.6	5.97	0.40
3400	21.0	6.41	0.37
4000	23.1	7.05	0.34
6000	29.4	8.95	0.27
8000	35.0	10.7	0.22
12400	45.9	14.0	0.17

Attenuation values are typical at ambient temperature +20°C (+68°F).

Power rating ambient temperature +40°C (+104°F), inner conductor +100°C (+212°F).

CODES FOR NKC CONNECTORS

CONNECTOR TYPE	NK CODE
N male	NKC2012300
N female	NKC2012400
7-16 male	NKC2012100
7-16 female	NKC2012200
N male Right angle	NKC2012600
7-16 male Right angle	NKC2012500